

E-Vision Laser 7500 WUXGA

7,500 Lumens | Contrast Ratio: 10,000:1 (Dynamic Black)1,800:1 native | Part No:117-917

E-VISION LASER 7500 DIGITAL PROJECTOR

THE VISIONARIES CHOICE



| | |
|--------------------------|---|
| Colour System: | DMD Specification: |
| Laser Phosphor | 1920 x 1200 pixels native display, Fast transit pixels for smooth greyscale and improved contrast. |
| Display Type: | Aspect Ratio: |
| 1 x 0.67" DarkChip™ DMD™ | 16x10 |
| | Fill Factor |
| | 87% |

Key Features

Video & Graphics Processing

- HDMI 1.4 for Side by Side, Frame Packing & Top Bottom 3D Formats.
- Dual Flash Processing can be used to multiply the displayed frame rate for 3D sources
- Dual Pipe Processing: Two sources in parallel for Left and Right Eyes.
- Synchronisation of active glasses.
- 3GSDI with loop-through.
- 24p and 1080p native display.
- DICOM Simulation Mode.

Geometry Correction

- Cornerstone, Vertical & Horizontal Keystone, Pincushion & Barrel, and Image Rotation.
- Blanking control for custom input window sizing.
- Scaling for fixed aspect ratio screens.

Edge Blending

- Correction for non-active pixels at the edge of the display.

Picture in Picture

- Two sources can be displayed either one within the other (PIP), or side by side, with original aspect ratios maintained.

HDBaseT® Interface

- Built in support for transmission of uncompressed High Definition Video over standard CAT5e/6 LAN cable.
- Allows projector to be placed up to 100m from source with low cost cabling.

Colour Processing

- Powerful seven point colour correction for accurate colour matching.

Projector Controller Software

- Intuitive user interface for network control
- Simultaneous control of user-defined groups of projectors
- At-a-glance monitoring of projector status

Projector Automation

- Real-time clock provides daily on/off automation.

Source Compatibility:

3GSDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.

HDMI including Deep Color™ processing.

Graphics standards up to 1920 x 1200 resolution at 60Hz via HDMI, DisplayPort or VGA.

Component Video (SD and HD) via RGBHV.

Inputs/Outputs

| Video & Computer | | | Communication & Control | | |
|------------------|--------------|-----|-------------------------|-------------------|-----|
| Type | Connector | Qty | Type | Connector | Qty |
| DisplayPort 1.1a | DisplayPort | 1 | 3D Sync Out | BNC | 1 |
| HDMI 1.4 | HDMI | 2 | 3D Sync In | BNC | 1 |
| 3G-SDI in | BNC | 1 | LAN | RJ45 | 1 |
| 3G-SDI out | BNC | 1 | RS232 | 9-pin D Sub | 1 |
| VGA / Analog RGB | 15-pin D-Sub | 1 | Wired Remote | 3.5mm Stereo Jack | 1 |
| Component Video | 5 x BNC | 1 | 12V Trigger | 3.5mm Stereo Jack | 2 |
| HDBaseT | LAN | 1 | Service Port | USB Type A | 1 |
| DVI-D with HDCP | DVI | 1 | | | |

3D Formats Supported

Frame Packing
Dual Pipe
Frame Sequential
Side By Side (half)
Top and Bottom

HDTV Formats Supported

1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz), 1080i (50Hz, 60Hz), 720p (50, 60Hz)

Computer Compatibility

Up to 1920 x 1200

Bandwidth

165 MHz on analog RGB
165 Megapixels per second on HDMI

Remote Control

Addressable IR remote control, wireless and wired.
On-Board keypad

Automation Control

Crestron RoomView® Connected
PJLink
LAN
RS232
AMX (Device Discovery)

Colour Temperature

User selectable from 5000 to 9300K

Lamp Type

Laser Light Source

Typical Lamp Life

20,000 hours

Lenses

| Lens | Part No. | Optimised Focus | Lens Shift |
|---------------------|----------|-----------------|--|
| 0.38 :1 fixed | 117-341 | 0.68m - 2.44m | none |
| 0.76 :1 fixed | 112-499 | 0.81m - 5.08m | none |
| 0.75 - 0.93 :1 zoom | 115-339 | 1.02m - 12.7m | Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame |
| 1.25 - 1.79 :1 zoom | 112-500 | 1.33m - 11.73m | Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame |
| 1.73 - 2.27 :1 zoom | 112-501 | 1.83m - 14.9m | Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame |
| 2.22 - 3.67 :1 zoom | 112-502 | 2.36m - 24.2m | Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame |
| 3.58 - 5.38 :1 zoom | 112-503 | 3.8m - 35.35m | Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame |
| 5.31 - 8.26 :1 zoom | 112-504 | 5.59m - 54.8m | Vert: 0.5 (U) 0.3 (D) frame, Hor: 0.1(L) 0.2 (R) frame |

* Lens focal ranges above are the optimised distances but are likely to focus further, please contact your RSM for more details. Lens ratio tolerances: E-Vision Series: +/-3%. HighLite Series: +/- 5%. M-Vision Series: +/- 2%. Titan Series: +/- 2%, INSIGHT Series: +/-2%,

Lens Mount

Motorised and programmable shift, zoom and focus.
Intelligent Lens Memory with 10 user-definable preset positions (except UST lens).

| | |
|--|--|
| Mechanical Mounting | Orientation |
| Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet | Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes |
| Power Requirements | Power Consumption |
| 100-240VAC 50/60Hz single phase | 815W |
| Thermal Dissipation | Fan Noise |
| 2780 BTU/Hour | 40 dBA |
| Operating/Storage Temperature | Operating Humidity |
| Operating: 0 to 40C (32 to 104F) Storage: -20 to 60C (-4 to 140F) | 10 to 90% non-condensing |
| Weight (Chassis Only) | Dimensions |
| 28 kg 62 lb | L: 59.83 cm W: 50.0 cm H: 21.85 cm |
| Safety & EMC Regulations | |
| CE, FCC Class A, UL, CCC | |

| | |
|---|-----------------|
| Accessories | |
| Accessory | Part No. |
| Infrared Remote (replacement) | 117-780 |
| <i>*Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.</i> | |

| | |
|----------------------------------|---------------------------------------|
| Downloads | |
| PDF CAD Drawings | User Guides |
| AUTOCAD Drawings | User Guides German |
| | User Guides French |
| | Important Information |



Certificate Number 13629
ISO 9001

Specifications subject to change without notice. Digital Projection version: - ©2016 Digital Projection.
DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc

DIGITAL PROJECTION, LTD GREENSIDE WAY, MIDDLETON MANCHESTER, UK. M24 1XX
T: +44.161.947.3300 | F: +44.161.684.7674 | www.digitalprojection.co.uk

DIGITAL PROJECTION, INC 55 CHASTAIN ROAD, SUITE 115 KENNESAW, GA. 30144
T: 770.420.1350 | F: 770.420.1360 | www.digitalprojection.com

DIGITAL PROJECTION, CHINA Rm A2006, ShaoYaoJu 101 North lane, Shi AO International Center, Chao Yang District, Beijing, 100029, PR CHINA
T: +86.10.58239771 | F: +86 10 58239770

DIGITAL PROJECTION, ASIA 16 NEW INDUSTRIAL ROAD, #02-10 HUDSON TECHNOCENTRE SINGAPORE 536204

T: +65.6284.1138 | F: +65.6284.1238